## Xelos 42 SL incl. DR+ Homestyle flatscreen design.

- Loewe LCD-TV with 106 cm screen diagonal and high definition Full-HD 100Hz Slim LCD technology.
- DVB-T, DVB-C, DVB-S (optional), HDTV reception and 250 GB hard disk memory integrated.
- Less than 105 cm in width.







## **Technical information**

### Image:

- 24p motion picture display
- Image resolution (in pixel): 1,920 x 1,080
- Horizontal and vertical viewing angle: 178° / 178°
- Picture format: 16:9
- Vertical image correction
- Screen diagonal in cm: 106
- Picture frequency 100Hz
- Format options: 16:9, 4:3, Panorama, Cinema, Zoom
- Full-HD 100Hz Slim LCD technology
- HD ready
- Integrated HDTV reception
- Image+ Active
- Contrast sensor
- Contrast ratio dynamic: 10,000 : 1
- Contrast ratio static: 1,300 : 1
- Brightness cd/m<sup>2</sup>: 500
- PIP (AV)/Full PIP/iPIP
- Response time: 5 ms
- Split Screen TV/Teletext [1] Fully digitised signal processing
- Audio:
- Number of speakers: 2
- Output in Watts (music/sine): 2x 20/2x 10
- Fullrange speakers
- Two-channel stereo sound
- Tone effects: Stereo, Panorama, 3D Surround

- Automatic station identification
- Radio function: with DVB-C/DVB-S [3]

#### Operation:

- Automatic shut-off
- Assist+
- Automatic Signal Switch (ASS)
- Automatic Volume Control (AVC) [4]
- Via control unit: 5 keys
- DR+ / Opslagcapaciteit 250 GB
- Digital Link
- Digital Link HD
- Digital Link Plus
- Electronic Program Guide (EPG): (analogue/digital) [2]
- Electronic Instruction Manual

- Favourites lists: 6
- Remote control: Assist 2
- Content-sensitive help
- Parental Lock Plus
- Power switch
- NexTView-Link [2]
- On Screen Display (OSD) foreign languages: D-E-F-I-GB-NL-P-PL-CZ-DK-S-HU-FIN-N-SLN-TR-SK-RUS-GR
- Personalised teletext with direct access to bookmarked pages
- PhotoViewer
- Channel-specific volume adaptation
- Programme positions (incl. AV and radio): 1,850
- Channel identification
- Index
- Current TV Programme [2]
- Teletext: TOP-/FLOF-Teletext/Level 2.5
- Teletext page memory: 2,000
- Video Time
- Automatic Channel Programming (ACP)

#### Reception:

- Decoding System Audio: MPEG
- Decoding System Video: MPEG 2/MPEG 4
- Colour standard: PAL, SECAM, NTSC, NTSC-V, PAL-V (60 Hz)
- Television standard: B/G, D/K, I, L, M, N
- Audio standard: FM Two-channel/AM, Nicam
- Tuner: DVB-T, DVB-C; analogue, cable, antenna [6]

#### Connectors:

- Antenna (analogue/digital): 1
- Audio In (cinch)
- Audio Out, controlled (cinch)
- Common Interface (CI+): 1
- Component (YUV) In
- Digital-Audio In (cinch)
- Digital-Audio Out (cinch)
- Euro-AV/Scart, of which the following number are Component Video Input-ready: 1
- Euro-AV/Scart, of which the following number are RGB-ready: 1
- Euro-AV/Scart, of which the following number are S-VHS/ Hi8-ready: 2
- Euro-AV/Scart total: 2
- HDMI including HDCP: 2

- Headphones: 3.5 mm
- Copy function Euro-AV <-> Euro-AV Copy function Front-AV --> Euro-AV
- S-Video In
- Side AV Video-/S-VHS, Hi8-ready
- USB In: 2
- VGA
- Video In (cinch)

#### Optional function upgrades:

- DVB-S 2 (Single Tuner) [7]
- DVB-S 2 (Twin-Tuner)
- MovieVision DR+
- RS 232 C / Motor control / IR-Link

- Set-up solutions: incl. manual rotation: Floor Stand A 37/42/47, Floor Stand 4 / incl. motorised rotation: Floor Stand 4 MU [5]
- Equipment board for Floor Stand A 32-47
- Standard feature: Table Stand (incl. manual rotation)
- VESA adapter: VESA A42/47
- Wall Mount: WM 57, WM Flex 52 L [5]


### Miscellaneous:


- Power consumption per annum (in KWh): 256
- Weight (approx.) in kg: 27.50
- Power consumption when switched on according to EN 62087 (in watts): 175 ■ Power consumption in watts when the set is turned off: 0
- Power consumption in standby mode in watts: 0.9
- Mains voltage: 220-240 V / 50/60 Hz VDE-safety standard (inspection seal)
- Technical specifications, delivery conditions, and other information

# are subject to change without notice. [1] Not with MPEG4.

- [2] Works only with channels broadcasting service information/ NexTView data.
- [3] DVB-S only with integrated DVB-S 2 (Tuner)
- [4] Function depends on signal format emitted by station.
  [5] Only in conjunction with a corresponding adapter, to be ordered
- separately.

  [6] Freeview variants available for UK
- [7] Not available with Freeview interactivity in UK







Wall Mount Flex 52 L